

RED

RIBBON SPECIFICATION SHEET

WAX

COLOUR

THERMAL TRANSFER RIBBON

UN020R is a Red premium wax ribbon, designed to work on a wide range of printers. It is suitable for printing on many different types of label stocks.

RIBBON PROPERTIES

INK TYPE	WAX
RIBBON THICKNESS	9.0±0.3µm
BASE FILM	POLYESTER (4.5±0.3µm)
COLOUR	Red
PRINT SPEED	UP TO 10"/SEC
INK MELT POINT	77°C
PRINTING ENERGY	12mJ/mm ²




IMAGE PROPERTIES

PANTONE COLOUR	192C
RECOMMENDED LABEL STOCKS	COATED PAPER, GLOSS PAPER, SYNTHETIC PAPER
USAGE CONDITIONS	5°C TO 35°C / 20% TO 80% RELATIVE HUMIDITY
STORAGE CONDITIONS	0°C TO 40°C / 20% TO 80% RELATIVE HUMIDITY



UNION CHEMICAL

NOTE : THE INFORMATION SHOWN ABOVE IS BASED UPON TESTS CARRIED OUT BY UNION CHEMICAL CO. LTD., AND IS BELIEVED TO BE RELIABLE. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE